

**ITT****Lowara****Windings Electrical Resistances Values - 4OS MOTORS****Three phase - 2 poles**

MOTOR TYPE	kW	HP	V	R [Ω] 20°C
4OS03T235	0,37	0,5	220	35,7
			230	
			240	
4OS05T235	0,55	0,75	220	27,3
			230	
			240	
4OS07T235	0,75	1	220	19,7
			230	
			240	
4OS11T235	1,1	1,5	220	14,1
			230	
			240	
4OS15T235	1,5	2	220	9,3
			230	
			240	
4OS22T235	2,2	3	220	7,5
			230	
			240	
4OS30T235	3	4	220	6,2
			230	
			240	
4OS40T235	4	5,5	220	4,6
			230	
			240	
4OS55T235	5,5	7,5	220	2,7
			230	
			240	
4OS75T235	7,5	10	220	1,9
			230	
			240	
4OS03T405	0,37	0,5	380	11,9
			400	
			415	
4OS05T405	0,55	0,75	380	9,1
			400	
			415	
4OS07T405	0,75	1	380	6,6
			400	
			415	
4OS11T405	1,1	1,5	380	4,7
			400	
			415	
4OS15T405	1,5	2	380	3,1
			400	
			415	
4OS22T405	2,2	3	380	2,5
			400	
			415	

MOTOR TYPE	kW	HP	V	R [Ω] 20°C
4OS30T405	3	4	380	2,1
			400	
			415	
4OS40T405	4	5,5	380	1,5
			400	
			415	
4OS55T405	5,5	7,5	380	0,9
			400	
			415	
4OS75T405	7,5	10	380	0,6
			400	
			415	